



FEATURES

- * Compact size D20 x 70mm
- * Focussed spot size <100µm
- * Variable focus
- * swiss quality, IP67
- * Polarity reversal protection
- * anodised alu-body

The IDT 3 series of laser diode modules is ideally suited to applications such as bore sighting, alignment, robot control, positioning and edge detection. They include precision optical and mechanical components enclosed in a black anodised aluminium body.

The IDT3 series incorporates an adjustable lens which can be used to focus the beam to a very small spot size. Power is connected to the module using the positive (white) and negative (brown) cables. The Positive pin is also connected to the modules case.

Specifications:

Available Wavelengths	635, 650, 670, 780, 808, 830, 850 nm
Available Powers	1 - 100 mW
Beam Size at aperture	1 x 2.5mm
Divergence (collimated beam)	<1mrad
Spot size (focussed beam)	<100µm
Ray Stability	0.01 mrad / °C
Operating voltage	12 - 24V DC
Operating current	30 - 120mA (Depending on laser power)
Operating temp.	-10°C to +40 °C
Storage temp.	-40°C to +80°C
MTTF	> 35'000 hours

Options:

Standard Collimation on 10m	S
Variable Focus	V
available with 4-6 VDC	6

Specify part numbers as follows: **IDT363505/S24**

IDT 3 series, wavelength 635nm, output power <5mW
Standard collimation, 12-24VDC

Accessories

Holders
 Line Generator
 Power supplies for VCC

